
Amazon Inspector

API Reference

API Version 2016-02-16



Amazon Inspector: API Reference

Copyright © 2016 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddAttributesToFindings	4
Request Syntax	4
Request Parameters	4
Response Syntax	4
Response Elements	4
Errors	5
Example	5
CreateAssessmentTarget	7
Request Syntax	7
Request Parameters	7
Response Syntax	7
Response Elements	7
Errors	8
Example	8
CreateAssessmentTemplate	10
Request Syntax	10
Request Parameters	10
Response Syntax	11
Response Elements	11
Errors	11
Example	11
CreateResourceGroup	13
Request Syntax	13
Request Parameters	13
Response Syntax	13
Response Elements	13
Errors	14
Example	14
DeleteAssessmentRun	16
Request Syntax	16
Request Parameters	16
Response Elements	16
Errors	16
Example	17
DeleteAssessmentTarget	18
Request Syntax	18
Request Parameters	18
Response Elements	18
Errors	18
Example	19
DeleteAssessmentTemplate	20
Request Syntax	20
Request Parameters	20
Response Elements	20
Errors	20
Example	21
DescribeAssessmentRuns	22
Request Syntax	22
Request Parameters	22
Response Syntax	22
Response Elements	23
Errors	23
Example	23

DescribeAssessmentTargets	26
Request Syntax	26
Request Parameters	26
Response Syntax	26
Response Elements	26
Errors	27
Example	27
DescribeAssessmentTemplates	29
Request Syntax	29
Request Parameters	29
Response Syntax	29
Response Elements	29
Errors	30
Example	30
DescribeCrossAccountAccessRole	32
Response Syntax	32
Response Elements	32
Errors	32
Example	32
DescribeFindings	34
Request Syntax	34
Request Parameters	34
Response Syntax	34
Response Elements	35
Errors	35
Example	36
DescribeResourceGroups	38
Request Syntax	38
Request Parameters	38
Response Syntax	38
Response Elements	38
Errors	39
Example	39
DescribeRulesPackages	41
Request Syntax	41
Request Parameters	41
Response Syntax	41
Response Elements	41
Errors	42
Example	42
GetTelemetryMetadata	44
Request Syntax	44
Request Parameters	44
Response Syntax	44
Response Elements	44
Errors	44
Example	45
ListAssessmentRunAgents	49
Request Syntax	49
Request Parameters	49
Response Syntax	49
Response Elements	50
Errors	50
Example	51
ListAssessmentRuns	55
Request Syntax	55
Request Parameters	55
Response Syntax	56

Response Elements	56
Errors	56
Example	57
ListAssessmentTargets	58
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	58
Errors	59
Example	59
ListAssessmentTemplates	61
Request Syntax	61
Request Parameters	61
Response Syntax	62
Response Elements	62
Errors	62
Example	62
ListEventSubscriptions	64
Request Syntax	64
Request Parameters	64
Response Syntax	64
Response Elements	65
Errors	65
Example	65
ListFindings	67
Request Syntax	67
Request Parameters	67
Response Syntax	68
Response Elements	68
Errors	68
Example	69
ListRulesPackages	70
Request Syntax	70
Request Parameters	70
Response Syntax	70
Response Elements	70
Errors	71
Example	71
ListTagsForResource	73
Request Syntax	73
Request Parameters	73
Response Syntax	73
Response Elements	73
Errors	73
Example	74
PreviewAgents	75
Request Syntax	75
Request Parameters	75
Response Syntax	75
Response Elements	75
Errors	76
Example	76
RegisterCrossAccountAccessRole	78
Request Syntax	78
Request Parameters	78
Response Elements	78
Errors	78
Example	79

RemoveAttributesFromFindings	80
Request Syntax	80
Request Parameters	80
Response Syntax	80
Response Elements	80
Errors	81
Example	81
SetTagsForResource	83
Request Syntax	83
Request Parameters	83
Response Elements	83
Errors	83
Example	84
StartAssessmentRun	85
Request Syntax	85
Request Parameters	85
Response Syntax	85
Response Elements	85
Errors	86
Example	86
StopAssessmentRun	88
Request Syntax	88
Request Parameters	88
Response Elements	88
Errors	88
Example	88
SubscribeToEvent	90
Request Syntax	90
Request Parameters	90
Response Elements	90
Errors	90
Example	91
UnsubscribeFromEvent	92
Request Syntax	92
Request Parameters	92
Response Elements	92
Errors	92
Example	93
UpdateAssessmentTarget	94
Request Syntax	94
Request Parameters	94
Response Elements	94
Errors	94
Example	95
Data Types	96
AgentAlreadyRunningAssessment	98
Contents	98
AgentFilter	99
Contents	99
AgentPreview	100
Contents	100
AssessmentRun	101
Contents	101
AssessmentRunAgent	103
Contents	103
AssessmentRunFilter	104
Contents	104
AssessmentRunNotification	106

Contents	106
AssessmentRunStateChange	107
Contents	107
AssessmentTarget	108
Contents	108
AssessmentTargetFilter	109
Contents	109
AssessmentTemplate	110
Contents	110
AssessmentTemplateFilter	111
Contents	111
AssetAttributes	112
Contents	112
Attribute	113
Contents	113
DurationRange	114
Contents	114
EventSubscription	115
Contents	115
FailedItemDetails	116
Contents	116
Finding	117
Contents	117
FindingFilter	119
Contents	119
InspectorServiceAttributes	121
Contents	121
ResourceGroup	122
Contents	122
ResourceGroupTag	123
Contents	123
RulesPackage	124
Contents	124
Subscription	125
Contents	125
Tag	126
Contents	126
TelemetryMetadata	127
Contents	127
TimestampRange	128
Contents	128
Common Parameters	129
Common Errors	131

Welcome

Amazon Inspector enables you to analyze the behavior of your AWS resources and to identify potential security issues. For more information, see [Amazon Inspector User Guide](#).

This document was last published on August 26, 2016.

Actions

The following actions are supported:

- [AddAttributesToFindings](#) (p. 4)
- [CreateAssessmentTarget](#) (p. 7)
- [CreateAssessmentTemplate](#) (p. 10)
- [CreateResourceGroup](#) (p. 13)
- [DeleteAssessmentRun](#) (p. 16)
- [DeleteAssessmentTarget](#) (p. 18)
- [DeleteAssessmentTemplate](#) (p. 20)
- [DescribeAssessmentRuns](#) (p. 22)
- [DescribeAssessmentTargets](#) (p. 26)
- [DescribeAssessmentTemplates](#) (p. 29)
- [DescribeCrossAccountAccessRole](#) (p. 32)
- [DescribeFindings](#) (p. 34)
- [DescribeResourceGroups](#) (p. 38)
- [DescribeRulesPackages](#) (p. 41)
- [GetTelemetryMetadata](#) (p. 44)
- [ListAssessmentRunAgents](#) (p. 49)
- [ListAssessmentRuns](#) (p. 55)
- [ListAssessmentTargets](#) (p. 58)
- [ListAssessmentTemplates](#) (p. 61)
- [ListEventSubscriptions](#) (p. 64)
- [ListFindings](#) (p. 67)
- [ListRulesPackages](#) (p. 70)
- [ListTagsForResource](#) (p. 73)
- [PreviewAgents](#) (p. 75)
- [RegisterCrossAccountAccessRole](#) (p. 78)

- [RemoveAttributesFromFindings](#) (p. 80)
- [SetTagsForResource](#) (p. 83)
- [StartAssessmentRun](#) (p. 85)
- [StopAssessmentRun](#) (p. 88)
- [SubscribeToEvent](#) (p. 90)
- [UnsubscribeFromEvent](#) (p. 92)
- [UpdateAssessmentTarget](#) (p. 94)

AddAttributesToFindings

Assigns attributes (key and value pairs) to the findings that are specified by the ARNs of the findings.

Request Syntax

```
{
  "attributes (p. 4)": [
    {
      "key (p. 113)": "string",
      "value (p. 113)": "string"
    }
  ],
  "findingArns (p. 4)": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

attributes (p. 4)

The array of attributes that you want to assign to specified findings.

Type: array of [Attribute \(p. 113\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

findingArns (p. 4)

The ARNs that specify the findings that you want to assign attributes to.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems (p. 4)": {
    "string" : {
      "failureCode (p. 116)": "string",
      "retryable (p. 116)": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 4)

Attribute details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 116) object map

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 131).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 189
X-Amz-Target: InspectorService.AddAttributesToFindings
X-Amz-Date: 20160329T233810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "attributes": [
    {
      "key": "Example",
      "value": "example"
    }
  ],
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-811VIE0D/run/0-Z02cjjug/finding/0-T8yM9mEU"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4c8b9c50-f607-11e5-9380-d76f0924b6d7
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:38:11 GMT
{
  "failedItems": {}
}
```

CreateAssessmentTarget

Creates a new assessment target using the ARN of the resource group that is generated by [CreateResourceGroup](#) (p. 13). You can create up to 50 assessment targets per AWS account. You can run up to 500 concurrent agents per AWS account. For more information, see [Amazon Inspector Assessment Targets](#).

Request Syntax

```
{  
  "assessmentTargetName (p. 7)": "string",  
  "resourceGroupArn (p. 7)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 129).

The request requires the following data in JSON format.

assessmentTargetName (p. 7)

The user-defined name that identifies the assessment target that you want to create. The name must be unique within the AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn (p. 7)

The ARN that specifies the resource group that is used to create the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentTargetArn (p. 7)": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArn (p. 7)

The ARN that specifies the assessment target that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 129
X-Amz-Target: InspectorService.CreateAssessmentTarget
X-Amz-Date: 20160331T174054Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetName": "ExampleAssessmentTarget",
  "resourceGroupArn": "arn:aws:inspector:us-west-
2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b87f981e-f767-11e5-82d7-bb83264505be
```

Amazon Inspector API Reference Example

```
Content-Type: application/x-amz-json-1.1
Content-Length: 84
Date: Thu, 31 Mar 2016 17:40:55 GMT
{
  "assessmentTargetArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX"
}
```


CreateAssessmentTemplate

Creates an assessment template for the assessment target that is specified by the ARN of the assessment target.

Request Syntax

```
{
  "assessmentTargetArn (p. 10)": "string",
  "assessmentTemplateName (p. 10)": "string",
  "durationInSeconds (p. 10)": number,
  "rulesPackageArns (p. 10)": [ "string" ],
  "userAttributesForFindings (p. 10)": [
    {
      "key (p. 113)": "string",
      "value (p. 113)": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTargetArn (p. 10)

The ARN that specifies the assessment target for which you want to create the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateName (p. 10)

The user-defined name that identifies the assessment template that you want to create. You can create several assessment templates for an assessment target. The names of the assessment templates that correspond to a particular assessment target must be unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

durationInSeconds (p. 10)

The duration of the assessment run in seconds. The default value is 3600 seconds (one hour).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

rulesPackageArns (p. 10)

The ARNs that specify the rules packages that you want to attach to the assessment template.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

userAttributesForFindings (p. 10)

The user-defined attributes that are assigned to every finding that is generated by the assessment run that uses this assessment template.

Type: array of [Attribute \(p. 113\)](#) objects
Array Members: Minimum number of 0 items. Maximum number of 10 items.
Required: No

Response Syntax

```
{  
  "assessmentTemplateArn (p. 11)": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.
The following data is returned in JSON format by the service.

[assessmentTemplateArn \(p. 11\)](#)

The ARN that specifies the assessment template that is created.
Type: String
Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.
HTTP Status Code: 400

InternalException

Internal server error.
HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.
HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.
HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.
HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
```

Amazon Inspector API Reference Example

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 335
X-Amz-Target: InspectorService.CreateAssessmentTemplate
X-Amz-Date: 20160331T175559Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX",
  "assessmentTemplateName": "ExampleAssessmentTemplate",
  "userAttributesForFindings": [
    {
      "key": "Example",
      "value": "example"
    }
  ],
  "durationInSeconds": 180,
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
11B9DBXp"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d3d3d58e-f769-11e5-9da0-9bde5220d15c
Content-Type: application/x-amz-json-1.1
Content-Length: 106
Date: Thu, 31 Mar 2016 17:56:00 GMT
{
  "assessmentTemplateArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

CreateResourceGroup

Creates a resource group using the specified set of tags (key and value pairs) that are used to select the EC2 instances to be included in an Amazon Inspector assessment target. The created resource group is then used to create an Amazon Inspector assessment target. For more information, see [CreateAssessmentTarget \(p. 7\)](#).

Request Syntax

```
{
  "resourceGroupTags (p. 13)": [
    {
      "key (p. 123)": "string",
      "value (p. 123)": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

[resourceGroupTags \(p. 13\)](#)

A collection of keys and an array of possible values,
[{"key":"key1","values":["Value1","Value2"]}, {"key":"Key2","values":["Value3"]}].

For example, [{"key":"Name","values":["TestEC2Instance"]}].

Type: array of [ResourceGroupTag \(p. 123\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{
  "resourceGroupArn (p. 13)": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourceGroupArn \(p. 13\)](#)

The ARN that specifies the resource group that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 67
X-Amz-Target: InspectorService.CreateResourceGroup
X-Amz-Date: 20160331T171757Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceGroupTags": [
    {
      "key": "Name",
      "value": "example"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 8416dfb4-f764-11e5-872a-fde3682789d5
Content-Type: application/x-amz-json-1.1
Content-Length: 88
```

Amazon Inspector API Reference Example

```
Date: Thu, 31 Mar 2016 17:17:58 GMT
{
  "resourceGroupArn": "arn:aws:inspector:us-west-
2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

DeleteAssessmentRun

Deletes the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{  
  "assessmentRunArn (p. 16)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunArn (p. 16)

The ARN that specifies the assessment run that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.DeleteAssessmentRun
X-Amz-Date: 20160331T183810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b8494bff-f76f-11e5-9d49-6dd670a2a95d
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:38:11 GMT
```


DeleteAssessmentTarget

Deletes the assessment target that is specified by the ARN of the assessment target.

Request Syntax

```
{  
  "assessmentTargetArn (p. 18)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTargetArn (p. 18)

The ARN that specifies the assessment target that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 85
X-Amz-Target: InspectorService.DeleteAssessmentTarget
X-Amz-Date: 20160331T184144Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 37dee3da-f770-11e5-b61e-e163adb0c30c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:41:45 GMT
```

DeleteAssessmentTemplate

Deletes the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{  
  "assessmentTemplateArn (p. 20)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTemplateArn (p. 20)

The ARN that specifies the assessment template that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 107
X-Amz-Target: InspectorService.DeleteAssessmentTemplate
X-Amz-Date: 20160331T184505Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTemplateArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: afcc2e7e-f770-11e5-8f9c-054cd1296cf6
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:45:06 GMT
```

DescribeAssessmentRuns

Describes the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{  
  "assessmentRunArns (p. 22)": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunArns (p. 22)

The ARN that specifies the assessment run that you want to describe.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentRuns (p. 23)": [  
    {  
      "arn (p. 101)": "string",  
      "assessmentTemplateArn (p. 101)": "string",  
      "completedAt (p. 101)": number,  
      "createdAt (p. 101)": number,  
      "dataCollected (p. 101)": boolean,  
      "durationInSeconds (p. 101)": number,  
      "name (p. 101)": "string",  
      "notifications (p. 101)": [  
        {  
          "date (p. 106)": number,  
          "error (p. 106)": boolean,  
          "event (p. 106)": "string",  
          "message (p. 106)": "string",  
          "snsPublishStatusCode (p. 106)": "string",  
          "snsTopicArn (p. 106)": "string"  
        }  
      ],  
      "rulesPackageArns (p. 101)": [ "string" ],  
      "startedAt (p. 102)": number,  
      "state (p. 102)": "string",  
      "stateChangedAt (p. 102)": number,  
      "stateChanges (p. 102)": [  
        {  
          "state (p. 107)": "string",  
          "stateChangedAt (p. 107)": number  
        }  
      ]  
    }  
  ]  
}
```

```
    },  
    ],  
    "userAttributesForFindings (p. 102)": [  
      {  
        "key (p. 113)": "string",  
        "value (p. 113)": "string"  
      }  
    ]  
  }  
],  
"failedItems (p. 23)": {  
  "string" : {  
    "failureCode (p. 116)": "string",  
    "retryable (p. 116)": boolean  
  }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response. The following data is returned in JSON format by the service.

assessmentRuns (p. 22)

Information about the assessment run.

Type: array of [AssessmentRun \(p. 101\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems (p. 22)

Assessment run details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails \(p. 116\)](#) object map

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
Host: inspector.us-west-2.amazonaws.com  
Accept-Encoding: identity  
Content-Length: 120  
X-Amz-Target: InspectorService.DescribeAssessmentRuns
```

Amazon Inspector API Reference Example

```
X-Amz-Date: 20160323T213431Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0834f495-f13f-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 1156
Date: Wed, 23 Mar 2016 21:34:32 GMT
{
  "assessmentRuns": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
      "assessmentTemplateArn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
      "completedAt": 1458680301.4,
      "createdAt": 1458680170.035,
      "dataCollected": true,
      "durationInSeconds": 3600,
      "name": "Run 1 for ExampleAssessmentTemplate",
      "notifications": [],
      "rulesPackageArns": [
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-X1KXtawP"
      ],
      "startedAt": 1458680170.161,
      "state": "COMPLETED",
      "stateChangedAt": 1458680301.4,
      "stateChanges": [
        {
          "state": "CREATED",
          "stateChangedAt": 1458680170.035
        },
        {
          "state": "START_DATA_COLLECTION_PENDING",
          "stateChangedAt": 1458680170.065
        },
        {
          "state": "START_DATA_COLLECTION_IN_PROGRESS",
          "stateChangedAt": 1458680170.096
        }
      ]
    }
  ]
}
```

Amazon Inspector API Reference Example

```
{
  "state": "COLLECTING_DATA",
  "stateChangedAt": 1458680170.161
},
{
  "state": "STOP_DATA_COLLECTION_PENDING",
  "stateChangedAt": 1458680239.883
},
{
  "state": "DATA_COLLECTED",
  "stateChangedAt": 1458680299.847
},
{
  "state": "EVALUATING_RULES",
  "stateChangedAt": 1458680300.099
},
{
  "state": "COMPLETED",
  "stateChangedAt": 1458680301.4
}
],
"userAttributesForFindings": []
}
],
"failedItems": {}
}
```


DescribeAssessmentTargets

Describes the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{  
  "assessmentTargetArns (p. 26)": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTargetArns (p. 26)

The ARNs that specifies the assessment targets that you want to describe.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentTargets (p. 26)": [  
    {  
      "arn (p. 108)": "string",  
      "createdAt (p. 108)": number,  
      "name (p. 108)": "string",  
      "resourceGroupArn (p. 108)": "string",  
      "updatedAt (p. 108)": number  
    }  
  ],  
  "failedItems (p. 27)": {  
    "string" : {  
      "failureCode (p. 116)": "string",  
      "retryable (p. 116)": boolean  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargets (p. 26)

Information about the assessment targets.

Type: array of [AssessmentTarget \(p. 108\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

[failedItems \(p. 26\)](#)

Assessment target details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails \(p. 116\)](#) object map

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 88
X-Amz-Target: InspectorService.DescribeAssessmentTargets
X-Amz-Date: 20160323T214315Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 407ddf01-f140-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 287
Date: Wed, 23 Mar 2016 21:43:16 GMT
{
  "assessmentTargets": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-
```

Amazon Inspector API Reference Example

```
0kFIPusq",
    "createdAt": 1458074191.459,
    "name": "ExampleAssessmentTarget",
    "resourceGroupArn": "arn:aws:inspector:us-west-
2:123456789012:resourcegroup/0-PyGXopAI",
    "updatedAt": 1458074191.459
  }
],
"failedItems": {}
}
```

DescribeAssessmentTemplates

Describes the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{
  "assessmentTemplateArns (p. 29)": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTemplateArns (p. 29)

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "assessmentTemplates (p. 30)": [
    {
      "arn (p. 110)": "string",
      "assessmentTargetArn (p. 110)": "string",
      "createdAt (p. 110)": number,
      "durationInSeconds (p. 110)": number,
      "name (p. 110)": "string",
      "rulesPackageArns (p. 110)": [ "string" ],
      "userAttributesForFindings (p. 110)": [
        {
          "key (p. 113)": "string",
          "value (p. 113)": "string"
        }
      ]
    }
  ],
  "failedItems (p. 30)": {
    "string" : {
      "failureCode (p. 116)": "string",
      "retryable (p. 116)": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTemplates \(p. 29\)](#)

Information about the assessment templates.

Type: array of [AssessmentTemplate \(p. 110\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

[failedItems \(p. 29\)](#)

Assessment template details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails \(p. 116\)](#) object map

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 110
X-Amz-Target: InspectorService.DescribeAssessmentTemplates
X-Amz-Date: 20160323T214822Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTemplateArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-
0kFIPusq/template/0-4r1V2mAw"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f73a449b-f140-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 422
```

Amazon Inspector API Reference Example

```
Date: Wed, 23 Mar 2016 21:48:23 GMT
{
  "assessmentTemplates": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
      "assessmentTargetArn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq",
      "createdAt": 1458074191.844,
      "durationInSeconds": 3600,
      "name": "ExampleAssessmentTemplate",
      "rulesPackageArns": [
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-XlKXtawP"
      ],
      "userAttributesForFindings": []
    }
  ],
  "failedItems": {}
}
```

DescribeCrossAccountAccessRole

Describes the IAM role that enables Amazon Inspector to access your AWS account.

Response Syntax

```
{
  "registeredAt (p. 32)": number,
  "roleArn (p. 32)": "string",
  "valid (p. 32)": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registeredAt (p. 32)

The date when the cross-account access role was registered.

Type: Timestamp

roleArn (p. 32)

The ARN that specifies the IAM role that Amazon Inspector uses to access your AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

valid (p. 32)

A Boolean value that specifies whether the IAM role has the necessary policies attached to enable Amazon Inspector to access your AWS account.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.DescribeCrossAccountAccessRole
X-Amz-Date: 20160323T215330Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
```

Amazon Inspector API Reference Example

```
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: aef491a7-f141-11e5-bf1e-bbcafffe8bf2e
Content-Type: application/x-amz-json-1.1
Content-Length: 99
Date: Wed, 23 Mar 2016 21:53:32 GMT
{
  "registeredAt": 1458069182.826,
  "roleArn": "arn:aws:iam::123456789012:role/inspector",
  "valid": true
}
```


DescribeFindings

Describes the findings that are specified by the ARNs of the findings.

Request Syntax

```
{
  "findingArns (p. 34)": [ "string" ],
  "locale (p. 34)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

findingArns (p. 34)

The ARN that specifies the finding that you want to describe.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale (p. 34)

The locale into which you want to translate a finding description, recommendation, and the short description that identifies the finding.

Type: String

Valid Values: EN_US

Required: No

Response Syntax

```
{
  "failedItems (p. 35)": {
    "string": {
      "failureCode (p. 116)": "string",
      "retryable (p. 116)": boolean
    }
  },
  "findings (p. 35)": [
    {
      "arn (p. 117)": "string",
      "assetAttributes (p. 117)": {
        "agentId (p. 112)": "string",
        "amiId (p. 112)": "string",
        "autoScalingGroup (p. 112)": "string",
        "hostname (p. 112)": "string",
        "ipv4Addresses (p. 112)": [ "string" ],
        "schemaVersion (p. 112)": number
      },
      "assetType (p. 117)": "string",
      "attributes (p. 117)": [
```

```
    {
      "key (p. 113)": "string",
      "value (p. 113)": "string"
    }
  ],
  "confidence (p. 117)": number,
  "createdAt (p. 117)": number,
  "description (p. 117)": "string",
  "id (p. 117)": "string",
  "indicatorOfCompromise (p. 117)": boolean,
  "numericSeverity (p. 118)": number,
  "recommendation (p. 118)": "string",
  "schemaVersion (p. 118)": number,
  "service (p. 118)": "string",
  "serviceAttributes (p. 118)": {
    "assessmentRunArn (p. 121)": "string",
    "rulesPackageArn (p. 121)": "string",
    "schemaVersion (p. 121)": number
  },
  "severity (p. 118)": "string",
  "title (p. 118)": "string",
  "updatedAt (p. 118)": number,
  "userAttributes (p. 118)": [
    {
      "key (p. 113)": "string",
      "value (p. 113)": "string"
    }
  ]
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 34)

Finding details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails \(p. 116\)](#) object map

findings (p. 34)

Information about the finding.

Type: array of [Finding \(p. 117\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 133
X-Amz-Target: InspectorService.DescribeFindings
X-Amz-Date: 20160323T215809Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 555dbc27-f142-11e5-9dc2-6746fe4b2002
Content-Type: application/x-amz-json-1.1
Content-Length: 892
Date: Wed, 23 Mar 2016 21:58:10 GMT
{
  "failedItems": {},
  "findings": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",
      "assetAttributes": {
        "ipv4Addresses": [],
        "schemaVersion": 1
      },
      "assetType": "ec2-instance",
      "attributes": [],
      "confidence": 10,
      "createdAt": 1458680301.37,
      "description": "Amazon Inspector did not find any potential security issues during this assessment.",
      "indicatorOfCompromise": false,
      "numericSeverity": 0,
      "recommendation": "No remediation needed.",
      "schemaVersion": 1,
      "service": "Inspector",
    }
  ]
}
```

Amazon Inspector API Reference Example

```
        "serviceAttributes": {
            "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
            "rulesPackageArn": "arn:aws:inspector:us-west-
2:758058086616:rulespackage/0-X1KXtawP",
            "schemaVersion": 1
        },
        "severity": "Informational",
        "title": "No potential security issues found",
        "updatedAt": 1458680301.37,
        "userAttributes": []
    }
]
}
```

DescribeResourceGroups

Describes the resource groups that are specified by the ARNs of the resource groups.

Request Syntax

```
{  
  "resourceGroupArns (p. 38)": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

resourceGroupArns (p. 38)

The ARN that specifies the resource group that you want to describe.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "failedItems (p. 38)": {  
    "string" : {  
      "failureCode (p. 116)": "string",  
      "retryable (p. 116)": boolean  
    }  
  },  
  "resourceGroups (p. 39)": [  
    {  
      "arn (p. 122)": "string",  
      "createdAt (p. 122)": number,  
      "tags (p. 122)": [  
        {  
          "key (p. 123)": "string",  
          "value (p. 123)": "string"  
        }  
      ]  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 38)

Resource group details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 116) object map

resourceGroups (p. 38)

Information about a resource group.

Type: array of [ResourceGroup](#) (p. 122) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 131).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 92
X-Amz-Target: InspectorService.DescribeResourceGroups
X-Amz-Date: 20160323T220453Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceGroupArns": [
    "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-
PyGXopAI"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4636d6a9-f143-11e5-9f03-eb6e194efa59
Content-Type: application/x-amz-json-1.1
Content-Length: 191
Date: Wed, 23 Mar 2016 22:04:54 GMT
{
```

Amazon Inspector API Reference Example

```
    "failedItems": {},
    "resourceGroups": [
      {
        "arn": "arn:aws:inspector:us-west-2:123456789012:resource
group/0-PyGXopAI",
        "createdAt": 1458074191.098,
        "tags": [
          {
            "key": "Name",
            "value": "example"
          }
        ]
      }
    ]
  }
}
```

DescribeRulesPackages

Describes the rules packages that are specified by the ARNs of the rules packages.

Request Syntax

```
{
  "locale (p. 41)": "string",
  "rulesPackageArns (p. 41)": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

locale (p. 41)

The locale that you want to translate a rules package description into.

Type: String

Valid Values: EN_US

Required: No

rulesPackageArns (p. 41)

The ARN that specifies the rules package that you want to describe.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems (p. 42)": {
    "string" : {
      "failureCode (p. 116)": "string",
      "retryable (p. 116)": boolean
    }
  },
  "rulesPackages (p. 42)": [
    {
      "arn (p. 124)": "string",
      "description (p. 124)": "string",
      "name (p. 124)": "string",
      "provider (p. 124)": "string",
      "version (p. 124)": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 41)

Rules package details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails \(p. 116\)](#) object map

rulesPackages (p. 41)

Information about the rules package.

Type: array of [RulesPackage \(p. 124\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 90
X-Amz-Target: InspectorService.DescribeRulesPackages
X-Amz-Date: 20160323T220919Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
9hgA516p"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e4a6aee0-f143-11e5-a5ad-73b7f19c946c
```

Amazon Inspector API Reference Example

```
Content-Type: application/x-amz-json-1.1
Content-Length: 387
Date: Wed, 23 Mar 2016 22:09:20 GMT
{
  "failedItems": {},
  "rulesPackages": [
    {
      "arn": "arn:aws:inspector:us-west-
2:758058086616:rulespackage/0-9hgA516p",
      "description": "The rules in this package help verify
whether the EC2 instances in your application are exposed to Common Vulnerabil
ities and
Exposures (CVEs). Attacks can exploit unpatched vulnerab
ilities to compromise the confidentiality, integrity, or availability of your
service
or data. The CVE system provides a reference for publicly
known information security vulnerabilities and exposures. For more information,
see
[https://cve.mitre.org/](https://cve.mitre.org/). If a
particular CVE appears in one of the produced Findings at the end of a completed
Inspector assessment, you can search [ht
tps://cve.mitre.org/](https://cve.mitre.org/) using the CVE's ID (for example,
\"CVE-2009-0021\") to
find detailed information about this CVE, its severity,
and how to mitigate it. ",
      "name": "Common Vulnerabilities and Exposures",
      "provider": "Amazon Web Services, Inc.",
      "version": "1.1"
    }
  ]
}
```

GetTelemetryMetadata

Information about the data that is collected for the specified assessment run.

Request Syntax

```
{  
  "assessmentRunArn (p. 44)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunArn (p. 44)

The ARN that specifies the assessment run that has the telemetry data that you want to obtain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "telemetryMetadata (p. 44)": [  
    {  
      "count (p. 127)": number,  
      "dataSize (p. 127)": number,  
      "messageType (p. 127)": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

telemetryMetadata (p. 44)

Telemetry details.

Type: array of [TelemetryMetadata \(p. 127\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.
HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.
HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.
HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.GetTelemetryMetadata
X-Amz-Date: 20160329T223852Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 03ffa82f-f5ff-11e5-9cf9-9fd5e2aef2f6
Content-Type: application/x-amz-json-1.1
Content-Length: 1990
Date: Tue, 29 Mar 2016 22:38:53 GMT
{
  "telemetryMetadata": [
    {
      "count": 2,
      "dataSize": 345,
      "messageType": "InspectorDuplicateProcess"
    },
    {
      "count": 3,
      "dataSize": 255,
```

```
    "messageType": "InspectorTimeEventMsg"
  },
  {
    "count": 4,
    "dataSize": 1082,
    "messageType": "InspectorNetworkInterface"
  },
  {
    "count": 2,
    "dataSize": 349,
    "messageType": "InspectorDnsEntry"
  },
  {
    "count": 11,
    "dataSize": 2514,
    "messageType": "InspectorDirectoryInfoMsg"
  },
  {
    "count": 1,
    "dataSize": 179,
    "messageType": "InspectorTcpV6ListeningPort"
  },
  {
    "count": 101,
    "dataSize": 10949,
    "messageType": "InspectorTerminal"
  },
  {
    "count": 26,
    "dataSize": 5916,
    "messageType": "InspectorUser"
  },
  {
    "count": 282,
    "dataSize": 32148,
    "messageType": "InspectorDynamicallyLoadedCodeModule"
  },
  {
    "count": 18,
    "dataSize": 10172,
    "messageType": "InspectorCreateProcess"
  },
  {
    "count": 3,
    "dataSize": 8001,
    "messageType": "InspectorProcessPerformance"
  },
  {
    "count": 1,
    "dataSize": 360,
    "messageType": "InspectorOperatingSystem"
  },
  {
    "count": 6,
    "dataSize": 546,
    "messageType": "InspectorStopProcess"
  },
  {
```

```
    "count": 1,  
    "dataSize": 1553,  
    "messageType": "InspectorInstanceMetaData"  
  },  
  {  
    "count": 2,  
    "dataSize": 434,  
    "messageType": "InspectorTcpV4Connection"  
  },  
  {  
    "count": 474,  
    "dataSize": 2960322,  
    "messageType": "InspectorPackageInfo"  
  },  
  {  
    "count": 3,  
    "dataSize": 2235,  
    "messageType": "InspectorSystemPerformance"  
  },  
  {  
    "count": 105,  
    "dataSize": 46048,  
    "messageType": "InspectorCodeModule"  
  },  
  {  
    "count": 1,  
    "dataSize": 182,  
    "messageType": "InspectorUdpV6ListeningPort"  
  },  
  {  
    "count": 2,  
    "dataSize": 371,  
    "messageType": "InspectorUdpV4ListeningPort"  
  },  
  {  
    "count": 18,  
    "dataSize": 8362,  
    "messageType": "InspectorKernelModule"  
  },  
  {  
    "count": 29,  
    "dataSize": 48788,  
    "messageType": "InspectorConfigurationInfo"  
  },  
  {  
    "count": 1,  
    "dataSize": 79,  
    "messageType": "InspectorMonitoringStart"  
  },  
  {  
    "count": 5,  
    "dataSize": 0,  
    "messageType": "InspectorSplitMsgBegin"  
  },  
  {  
    "count": 51,  
    "dataSize": 4593,  
    "messageType": "InspectorGroup"
```

```
    },  
    {  
      "count": 1,  
      "dataSize": 184,  
      "messageType": "InspectorTcpV4ListeningPort"  
    },  
    {  
      "count": 1159,  
      "dataSize": 3146579,  
      "messageType": "Total"  
    },  
    {  
      "count": 5,  
      "dataSize": 0,  
      "messageType": "InspectorSplitMsgEnd"  
    },  
    {  
      "count": 1,  
      "dataSize": 612,  
      "messageType": "InspectorLoadImageInProgress"  
    }  
  ]  
}
```

ListAssessmentRunAgents

Lists the agents of the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArn (p. 49)": "string",
  "filter (p. 49)": {
    "agentHealthCodes (p. 99)": [ "string" ],
    "agentHealths (p. 99)": [ "string" ]
  },
  "maxResults (p. 49)": number,
  "nextToken (p. 49)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunArn (p. 49)

The ARN that specifies the assessment run whose agents you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

filter (p. 49)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AgentFilter \(p. 99\)](#) object

Required: No

maxResults (p. 49)

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 49)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRunAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentRunAgents (p. 50)": [
```



```
{
  "agentHealth (p. 103)": "string",
  "agentHealthCode (p. 103)": "string",
  "agentHealthDetails (p. 103)": "string",
  "agentId (p. 103)": "string",
  "assessmentRunArn (p. 103)": "string",
  "autoScalingGroup (p. 103)": "string",
  "telemetryMetadata (p. 103)": [
    {
      "count (p. 127)": number,
      "dataSize (p. 127)": number,
      "messageType (p. 127)": "string"
    }
  ],
  "nextToken (p. 50)": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunAgents (p. 49)

A list of ARNs that specifies the agents returned by the action.

Type: array of [AssessmentRunAgent \(p. 103\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

nextToken (p. 49)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.ListAssessmentRunAgents
X-Amz-Date: 20160323T212138Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3b752481-f13d-11e5-9f2a-87dc3189b81c
Content-Type: application/x-amz-json-1.1
Content-Length: 2206
Date: Wed, 23 Mar 2016 21:21:39 GMT
{
  "assessmentRunAgents": [
    {
      "agentHealth": "HEALTHY",
      "agentHealthCode": "HEALTHY",
      "agentId": "i-49113b93",
      "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
      "telemetryMetadata": [
        {
          "count": 2,
          "dataSize": 345,
          "messageType": "InspectorDuplicateProcess"
        },
        {
          "count": 3,
          "dataSize": 255,
          "messageType": "InspectorTimeEventMsg"
        },
        {
          "count": 4,
          "dataSize": 1082,
          "messageType": "InspectorNetworkInterface"
        }
      ]
    }
  ]
}
```

```
    },
    {
      "count": 2,
      "dataSize": 349,
      "messageType": "InspectorDnsEntry"
    },
    {
      "count": 11,
      "dataSize": 2514,
      "messageType": "InspectorDirectoryInfoMsg"
    },
    {
      "count": 1,
      "dataSize": 179,
      "messageType": "InspectorTcpV6ListeningPort"
    },
    {
      "count": 101,
      "dataSize": 10949,
      "messageType": "InspectorTerminal"
    },
    {
      "count": 26,
      "dataSize": 5916,
      "messageType": "InspectorUser"
    },
    {
      "count": 282,
      "dataSize": 32148,
      "messageType": "InspectorDynamicallyLoadedCodeModule"
    },
    {
      "count": 18,
      "dataSize": 10172,
      "messageType": "InspectorCreateProcess"
    },
    {
      "count": 3,
      "dataSize": 8001,
      "messageType": "InspectorProcessPerformance"
    },
    {
      "count": 1,
      "dataSize": 360,
      "messageType": "InspectorOperatingSystem"
    },
    {
      "count": 6,
      "dataSize": 546,
      "messageType": "InspectorStopProcess"
    },
    {
      "count": 1,
      "dataSize": 1553,
      "messageType": "InspectorInstanceMetaData"
    },
    {
```

Amazon Inspector API Reference

Example

```
    "count": 2,
    "dataSize": 434,
    "messageType": "InspectorTcpV4Connection"
  },
  {
    "count": 474,
    "dataSize": 2960322,
    "messageType": "InspectorPackageInfo"
  },
  {
    "count": 3,
    "dataSize": 2235,
    "messageType": "InspectorSystemPerformance"
  },
  {
    "count": 105,
    "dataSize": 46048,
    "messageType": "InspectorCodeModule"
  },
  {
    "count": 1,
    "dataSize": 182,
    "messageType": "InspectorUdpV6ListeningPort"
  },
  {
    "count": 2,
    "dataSize": 371,
    "messageType": "InspectorUdpV4ListeningPort"
  },
  {
    "count": 18,
    "dataSize": 8362,
    "messageType": "InspectorKernelModule"
  },
  {
    "count": 29,
    "dataSize": 48788,
    "messageType": "InspectorConfigurationInfo"
  },
  {
    "count": 1,
    "dataSize": 79,
    "messageType": "InspectorMonitoringStart"
  },
  {
    "count": 5,
    "dataSize": 0,
    "messageType": "InspectorSplitMsgBegin"
  },
  {
    "count": 51,
    "dataSize": 4593,
    "messageType": "InspectorGroup"
  },
  {
    "count": 1,
    "dataSize": 184,
    "messageType": "InspectorTcpV4ListeningPort"
```

Amazon Inspector API Reference Example

```
    },  
    {  
      "count": 1159,  
      "dataSize": 3146579,  
      "messageType": "Total"  
    },  
    {  
      "count": 5,  
      "dataSize": 0,  
      "messageType": "InspectorSplitMsgEnd"  
    },  
    {  
      "count": 1,  
      "dataSize": 612,  
      "messageType": "InspectorLoadImageInProgress"  
    }  
  ]  
}
```

ListAssessmentRuns

Lists the assessment runs that correspond to the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{
  "assessmentTemplateArns (p. 55)": [ "string" ],
  "filter (p. 55)": {
    "completionTimeRange (p. 104)": {
      "beginDate (p. 128)": number,
      "endDate (p. 128)": number
    },
    "durationRange (p. 104)": {
      "maxSeconds (p. 114)": number,
      "minSeconds (p. 114)": number
    },
    "namePattern (p. 104)": "string",
    "rulesPackageArns (p. 104)": [ "string" ],
    "startTimeRange (p. 104)": {
      "beginDate (p. 128)": number,
      "endDate (p. 128)": number
    },
    "stateChangeTimeRange (p. 104)": {
      "beginDate (p. 128)": number,
      "endDate (p. 128)": number
    },
    "states (p. 104)": [ "string" ]
  },
  "maxResults (p. 56)": number,
  "nextToken (p. 56)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTemplateArns (p. 55)

The ARNs that specify the assessment templates whose assessment runs you want to list.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter (p. 55)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentRunFilter \(p. 104\)](#) object

Required: No

maxResults (p. 55)

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 55)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRuns** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentRunArns (p. 56)": [ "string" ],
  "nextToken (p. 56)": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response. The following data is returned in JSON format by the service.

assessmentRunArns (p. 56)

A list of ARNs that specifies the assessment runs that are returned by the action.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 56)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 131).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentRuns
X-Amz-Date: 20160323T194135Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 410dabf6-f12f-11e5-8b5a-810259c0c3ae
Content-Type: application/x-amz-json-1.1
Content-Length: 215
Date: Wed, 23 Mar 2016 19:41:36 GMT
{
  "assessmentRunArns":
  [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE" ,
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-v5D6fI3v"
  ]
}
```


ListAssessmentTargets

Lists the ARNs of the assessment targets within this AWS account. For more information about assessment targets, see [Amazon Inspector Assessment Targets](#).

Request Syntax

```
{
  "filter (p. 58)": {
    "assessmentTargetNamePattern (p. 109)": "string"
  },
  "maxResults (p. 58)": number,
  "nextToken (p. 58)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

filter (p. 58)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTargetFilter \(p. 109\)](#) object

Required: No

maxResults (p. 58)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 58)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTargets** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentTargetArns (p. 59)": [ "string" ],
  "nextToken (p. 59)": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArns (p. 58)

A list of ARNs that specifies the assessment targets that are returned by the action.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 58)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTargets
X-Amz-Date: 20160323T201018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
```

Amazon Inspector API Reference Example

```
x-amzn-RequestId: 445f71f6-f133-11e5-932b-dd9c937d073a
Content-Type: application/x-amz-json-1.1
Content-Length: 87
Date: Wed, 23 Mar 2016 20:10:19 GMT
{
  "assessmentTargetArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
  ]
}
```

ListAssessmentTemplates

Lists the assessment templates that correspond to the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{
  "assessmentTargetArns (p. 61)": [ "string" ],
  "filter (p. 61)": {
    "durationRange (p. 111)": {
      "maxSeconds (p. 114)": number,
      "minSeconds (p. 114)": number
    },
    "namePattern (p. 111)": "string",
    "rulesPackageArns (p. 111)": [ "string" ]
  },
  "maxResults (p. 61)": number,
  "nextToken (p. 61)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTargetArns (p. 61)

A list of ARNs that specifies the assessment targets whose assessment templates you want to list.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter (p. 61)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTemplateFilter \(p. 111\)](#) object

Required: No

maxResults (p. 61)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 61)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTemplates** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "assessmentTemplateArns (p. 62)": [ "string" ],  
  "nextToken (p. 62)": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTemplateArns (p. 62)

A list of ARNs that specifies the assessment templates returned by the action.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 62)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1  
Host: inspector.us-west-2.amazonaws.com
```

Amazon Inspector API Reference Example

```
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTemplates
X-Amz-Date: 20160323T202549Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6f406528-f135-11e5-aa71-8de73166bfa9
Content-Type: application/x-amz-json-1.1
Content-Length: 190
Date: Wed, 23 Mar 2016 20:25:50 GMT
{
  "assessmentTemplateArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-Uza6ihLh"
  ]
}
```

ListEventSubscriptions

Lists all the event subscriptions for the assessment template that is specified by the ARN of the assessment template. For more information, see [SubscribeToEvent \(p. 90\)](#) and [UnsubscribeFromEvent \(p. 92\)](#).

Request Syntax

```
{  
  "maxResults (p. 64)": number,  
  "nextToken (p. 64)": "string",  
  "resourceArn (p. 64)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

maxResults (p. 64)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 64)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListEventSubscriptions** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

resourceArn (p. 64)

The ARN of the assessment template for which you want to list the existing event subscriptions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "nextToken (p. 65)": "string",  
  "subscriptions (p. 65)": [  
    {  
      "eventSubscriptions (p. 125)": [  
        {  
          "event (p. 115)": "string",  
          "subscribedAt (p. 115)": number  
        }  
      ],  
      "resourceArn (p. 125)": "string",  
      "topicArn (p. 125)": "string"  
    }  
  ]  
}
```

```
}  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response. The following data is returned in JSON format by the service.

nextToken (p. 64)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

subscriptions (p. 64)

Details of the returned event subscriptions.

Type: array of [Subscription](#) (p. 125) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 131).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1  
Host: inspector.us-west-2.amazonaws.com  
Accept-Encoding: identity  
Content-Length: 97  
X-Amz-Target: InspectorService.ListEventSubscriptions  
X-Amz-Date: 20160331T202943Z  
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
```



```
core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4e21c005-f77f-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 272
Date: Thu, 31 Mar 2016 20:29:44 GMT
{
  "subscriptions": [
    {
      "eventSubscriptions": [
        {
          "event": "ASSESSMENT_RUN_COMPLETED",
          "subscribedAt": 1459455440.867
        }
      ],
      "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
      "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
    }
  ]
}
```

ListFindings

Lists findings that are generated by the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArns (p. 67)": [ "string" ],
  "filter (p. 67)": {
    "agentIds (p. 119)": [ "string" ],
    "attributes (p. 119)": [
      {
        "key (p. 113)": "string",
        "value (p. 113)": "string"
      }
    ],
    "autoScalingGroups (p. 119)": [ "string" ],
    "creationTimeRange (p. 119)": {
      "beginDate (p. 128)": number,
      "endDate (p. 128)": number
    },
    "ruleNames (p. 119)": [ "string" ],
    "rulesPackageArns (p. 119)": [ "string" ],
    "severities (p. 119)": [ "string" ],
    "userAttributes (p. 120)": [
      {
        "key (p. 113)": "string",
        "value (p. 113)": "string"
      }
    ]
  },
  "maxResults (p. 68)": number,
  "nextToken (p. 68)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunArns (p. 67)

The ARNs of the assessment runs that generate the findings that you want to list.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter (p. 67)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [FindingFilter \(p. 119\)](#) object

Required: No

maxResults (p. 67)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 67)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListFindings** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "findingArns (p. 68)": [ "string" ],
  "nextToken (p. 68)": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response. The following data is returned in JSON format by the service.

findingArns (p. 68)

A list of ARNs that specifies the findings returned by the action.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 68)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListFindings
X-Amz-Date: 20160323T203109Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2df2e847-f136-11e5-b2c3-cd62ea256ca4
Content-Type: application/x-amz-json-1.1
Content-Length: 247
Date: Wed, 23 Mar 2016 20:31:10 GMT
{
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-v5D6fI3v/finding/0-tyvmqBLY"
  ]
}
```

ListRulesPackages

Lists all available Amazon Inspector rules packages.

Request Syntax

```
{  
  "maxResults (p. 70)": number,  
  "nextToken (p. 70)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

maxResults (p. 70)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 70)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListRulesPackages** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "nextToken (p. 70)": "string",  
  "rulesPackageArns (p. 70)": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 70)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

rulesPackageArns (p. 70)

The list of ARNs that specifies the rules packages returned by the action.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.
Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListRulesPackages
X-Amz-Date: 20160323T203727Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0e3779a9-f137-11e5-be28-e130082e2a98
Content-Type: application/x-amz-json-1.1
Content-Length: 424
Date: Wed, 23 Mar 2016 20:37:26 GMT
{
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
9hgA516p",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-
H5hpSawc",
```

Amazon Inspector API Reference Example

```
JJ0tZiqQ",      "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-  
vg5GGHSD"      "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-  
                ]  
                }
```

ListTagsForResource

Lists all tags associated with an assessment template.

Request Syntax

```
{  
  "resourceArn (p. 73)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

resourceArn (p. 73)

The ARN that specifies the assessment template whose tags you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "tags (p. 73)": [  
    {  
      "key (p. 126)": "string",  
      "value (p. 126)": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags (p. 73)

A collection of key and value pairs.

Type: array of [Tag \(p. 126\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListTagsForResource
X-Amz-Date: 20160323T212838Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-gcwFliYu"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3580d562-f13e-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 50
Date: Wed, 23 Mar 2016 21:28:39 GMT
{
  "tags": [
    {
      "key": "Name",
      "value": "Example"
    }
  ]
}
```

PreviewAgents

Previews the agents installed on the EC2 instances that are part of the specified assessment target.

Request Syntax

```
{
  "maxResults (p. 75)": number,
  "nextToken (p. 75)": "string",
  "previewAgentsArn (p. 75)": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

maxResults (p. 75)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 75)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **PreviewAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

previewAgentsArn (p. 75)

The ARN of the assessment target whose agents you want to preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "agentPreviews (p. 76)": [
    {
      "agentId (p. 100)": "string",
      "autoScalingGroup (p. 100)": "string"
    }
  ],
  "nextToken (p. 76)": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentPreviews (p. 75)

The resulting list of agents.

Type: array of [AgentPreview \(p. 100\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken (p. 75)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
core/1.4.3

POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 82
X-Amz-Target: InspectorService.PreviewAgents
X-Amz-Date: 20160329T224634Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
```

```
{
  "previewAgentsArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 176c8915-f600-11e5-ac8a-bb6015f4022c
Content-Type: application/x-amz-json-1.1
Content-Length: 44
Date: Tue, 29 Mar 2016 22:46:36 GMT
{
  "agentPreviews": [
    {
      "agentId": "i-49113b93"
    }
  ]
}
```

RegisterCrossAccountAccessRole

Registers the IAM role that Amazon Inspector uses to list your EC2 instances at the start of the assessment run or when you call the [PreviewAgents \(p. 75\)](#) action.

Request Syntax

```
{  
  "roleArn (p. 78)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

roleArn (p. 78)

The ARN of the IAM role that Amazon Inspector uses to list your EC2 instances during the assessment run or when you call the [PreviewAgents \(p. 75\)](#) action.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Example

Sample Request

```
core/1.4.3

POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 55
X-Amz-Target: InspectorService.RegisterCrossAccountAccessRole

X-Amz-Date: 20160329T225544Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "roleArn": "arn:aws:iam::123456789012:role/inspector"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 5f553cfa-f601-11e5-a47c-b7e2de2d572c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Tue, 29 Mar 2016 22:55:46 GMT
```

RemoveAttributesFromFindings

Removes entire attributes (key and value pairs) from the findings that are specified by the ARNs of the findings where an attribute with the specified key exists.

Request Syntax

```
{
  "attributeKeys (p. 80)": [ "string" ],
  "findingArns (p. 80)": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

attributeKeys (p. 80)

The array of attribute keys that you want to remove from specified findings.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

findingArns (p. 80)

The ARNs that specify the findings that you want to remove attributes from.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems (p. 80)": {
    "string" : {
      "failureCode (p. 116)": "string",
      "retryable (p. 116)": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 80)

Attributes details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails \(p. 116\)](#) object map

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 181
X-Amz-Target: InspectorService.RemoveAttributesFromFindings
X-Amz-Date: 20160329T234159Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "attributeKeys": [
    "key=Example,value=example"
  ],
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-
0kFIPusq/template/0-811VIE0D/run/0-Z02cjjug/finding/0-T8yM9mEU"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d4ebb8cf-f607-11e5-94d7-d9eab7a1ae2a
Content-Type: application/x-amz-json-1.1
```


Amazon Inspector API Reference Example

```
Content-Length: 18
Date: Tue, 29 Mar 2016 23:42:00 GMT
{
  "failedItems": {}
}
```

SetTagsForResource

Sets tags (key and value pairs) to the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{
  "resourceArn (p. 83)": "string",
  "tags (p. 83)": [
    {
      "key (p. 126)": "string",
      "value (p. 126)": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

resourceArn (p. 83)

The ARN of the assessment template that you want to set tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

tags (p. 83)

A collection of key and value pairs that you want to set to the assessment template.

Type: array of [Tag \(p. 126\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 144
X-Amz-Target: InspectorService.SetTagsForResource
X-Amz-Date: 20160331T185018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
  "tags": [
    {
      "key": "Example",
      "value": "example"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6a3f5af3-f771-11e5-8599-f1b50afafb5a
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:50:18 GMT
```

StartAssessmentRun

Starts the assessment run specified by the ARN of the assessment template. For this API to function properly, you must not exceed the limit of running up to 500 concurrent agents per AWS account.

Request Syntax

```
{  
  "assessmentRunName (p. 85)": "string",  
  "assessmentTemplateArn (p. 85)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunName (p. 85)

You can specify the name for the assessment run, or you can use the auto-generated name that is based on the assessment template name. The name must be unique for the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

assessmentTemplateArn (p. 85)

The ARN of the assessment template of the assessment run that you want to start.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentRunArn (p. 85)": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunArn (p. 85)

The ARN of the assessment run that has been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

AgentsAlreadyRunningAssessmentException

You started an assessment run, but one of the instances is already participating in another assessment run.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 142
X-Amz-Target: InspectorService.StartAssessmentRun
X-Amz-Date: 20160331T182519Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunName": "examplerun",
  "assessmentTemplateArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: ed349455-f76d-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 116
Date: Thu, 31 Mar 2016 18:25:22 GMT
{
  "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-jOoroxyY"
}
```

StopAssessmentRun

Stops the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{  
  "assessmentRunArn (p. 88)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentRunArn (p. 88)

The ARN of the assessment run that you want to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
```

Amazon Inspector API Reference Example

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.StopAssessmentRun
X-Amz-Date: 20160331T183401Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 23e1a935-f76f-11e5-92d3-7ba54a65df23
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:34:02 GMT
```


SubscribeToEvent

Enables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{  
  "event (p. 90)": "string",  
  "resourceArn (p. 90)": "string",  
  "topicArn (p. 90)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

event (p. 90)

The event for which you want to receive SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED |
ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn (p. 90)

The ARN of the assessment template that is used during the event for which you want to receive SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn (p. 90)

The ARN of the SNS topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.
HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.
HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.
HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.SubscribeToEvent
X-Amz-Date: 20160331T201719Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
  "event": "ASSESSMENT_RUN_COMPLETED",
  "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 929b6c44-f77d-11e5-bcc6-cd3a7bd10be0
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:17:20 GMT
```

UnsubscribeFromEvent

Disables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{  
  "event (p. 92)": "string",  
  "resourceArn (p. 92)": "string",  
  "topicArn (p. 92)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

event (p. 92)

The event for which you want to stop receiving SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn (p. 92)

The ARN of the assessment template that is used during the event for which you want to stop receiving SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn (p. 92)

The ARN of the SNS topic to which SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.
HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.
HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.UnsubscribeFromEvent
X-Amz-Date: 20160331T203404Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
  "event": "ASSESSMENT_RUN_COMPLETED",
  "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e9c2e864-f77f-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:34:06 GMT
```

UpdateAssessmentTarget

Updates the assessment target that is specified by the ARN of the assessment target.

Request Syntax

```
{  
  "assessmentTargetArn (p. 94)": "string",  
  "assessmentTargetName (p. 94)": "string",  
  "resourceGroupArn (p. 94)": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 129\)](#).

The request requires the following data in JSON format.

assessmentTargetArn (p. 94)

The ARN of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTargetName (p. 94)

The name of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn (p. 94)

The ARN of the resource group that is used to specify the new resource group to associate with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 131\)](#).

AccessDeniedException

You do not have required permissions to access the requested resource.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Example

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 206
X-Amz-Target: InspectorService.UpdateAssessmentTarget
X-Amz-Date: 20160331T185748Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 boto
core/1.4.3

Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-west-
2:123456789012:target/0-nvgVhaxX",
  "assessmentTargetName": "Example",
  "resourceGroupArn": "arn:aws:inspector:us-west-
2:123456789012:resourcegroup/0-yNbgL5Pt"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 76bc43e7-f772-11e5-a5f3-fb6257e71620
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:57:49 GMT
```

Data Types

The Amazon Inspector API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AgentAlreadyRunningAssessment](#) (p. 98)
- [AgentFilter](#) (p. 99)
- [AgentPreview](#) (p. 100)
- [AssessmentRun](#) (p. 101)
- [AssessmentRunAgent](#) (p. 103)
- [AssessmentRunFilter](#) (p. 104)
- [AssessmentRunNotification](#) (p. 106)
- [AssessmentRunStateChange](#) (p. 107)
- [AssessmentTarget](#) (p. 108)
- [AssessmentTargetFilter](#) (p. 109)
- [AssessmentTemplate](#) (p. 110)
- [AssessmentTemplateFilter](#) (p. 111)
- [AssetAttributes](#) (p. 112)
- [Attribute](#) (p. 113)
- [DurationRange](#) (p. 114)
- [EventSubscription](#) (p. 115)
- [FailedItemDetails](#) (p. 116)
- [Finding](#) (p. 117)
- [FindingFilter](#) (p. 119)
- [InspectorServiceAttributes](#) (p. 121)
- [ResourceGroup](#) (p. 122)

- [ResourceGroupTag](#) (p. 123)
- [RulesPackage](#) (p. 124)
- [Subscription](#) (p. 125)
- [Tag](#) (p. 126)
- [TelemetryMetadata](#) (p. 127)
- [TimestampRange](#) (p. 128)

AgentAlreadyRunningAssessment

Used in the exception error that is thrown if you start an assessment run for an assessment target that includes an EC2 instance that is already participating in another started assessment run.

Contents

agentId

ID of the agent that is running on an EC2 instance that is already participating in another started assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that has already been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

AgentFilter

Contains information about an Amazon Inspector agent. This data type is used as a request parameter in the [ListAssessmentRunAgents](#) (p. 49) action.

Contents

agentHealthCodes

The detailed health state of the agent. Values can be set to **IDLE**, **RUNNING**, **SHUTDOWN**, **UNHEALTHY**, **THROTTLED**, and **UNKNOWN**.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: `IDLE` | `RUNNING` | `SHUTDOWN` | `UNHEALTHY` | `THROTTLED` | `UNKNOWN`

Required: Yes

agentHealths

The current health state of the agent. Values can be set to **HEALTHY** or **UNHEALTHY**.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: `HEALTHY` | `UNHEALTHY`

Required: Yes

AgentPreview

Used as a response element in the [PreviewAgents \(p. 75\)](#) action.

Contents

agentId

The ID of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

autoScalingGroup

The Auto Scaling group for the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

AssessmentRun

A snapshot of an Amazon Inspector assessment run that contains the findings of the assessment run . Used as the response element in the [DescribeAssessmentRuns \(p. 22\)](#) action.

Contents

arn

The ARN of the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateArn

The ARN of the assessment template that is associated with the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

completedAt

The assessment run completion time that corresponds to the rules packages evaluation completion time or failure.

Type: Timestamp

Required: No

createdAt

The time when [StartAssessmentRun \(p. 85\)](#) was called.

Type: Timestamp

Required: Yes

dataCollected

A Boolean value (true or false) that specifies whether the process of collecting data from the agents is completed.

Type: Boolean

Required: Yes

durationInSeconds

The duration of the assessment run.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

name

The auto-generated name for the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

notifications

A list of notifications for the event subscriptions. A notification about a particular generated finding is added to this list only once.

Type: array of [AssessmentRunNotification \(p. 106\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

rulesPackageArns

The rules packages selected for the assessment run.

Type: array of Strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

startedAt

The time when [StartAssessmentRun \(p. 85\)](#) was called.

Type: Timestamp

Required: No

state

The state of the assessment run.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING |
START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA |
STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | EVALUATING_RULES | FAILED
| COMPLETED | COMPLETED_WITH_ERRORS

Required: Yes

stateChangedAt

The last time when the assessment run's state changed.

Type: Timestamp

Required: Yes

stateChanges

A list of the assessment run state changes.

Type: array of [AssessmentRunStateChange \(p. 107\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding.

Type: array of [Attribute \(p. 113\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

AssessmentRunAgent

Contains information about an Amazon Inspector agent. This data type is used as a response element in the [ListAssessmentRunAgents](#) (p. 49) action.

Contents

agentHealth

The current health state of the agent.

Type: String

Valid Values: HEALTHY | UNHEALTHY

Required: Yes

agentHealthCode

The detailed health state of the agent.

Type: String

Valid Values: IDLE | RUNNING | SHUTDOWN | UNHEALTHY | THROTTLED | UNKNOWN

Required: Yes

agentHealthDetails

The description for the agent health code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

agentId

The AWS account of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that is associated with the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

autoScalingGroup

The Auto Scaling group of the EC2 instance that is specified by the agent ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

telemetryMetadata

The Amazon Inspector application data metrics that are collected by the agent.

Type: array of [TelemetryMetadata](#) (p. 127) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Required: Yes

AssessmentRunFilter

Used as the request parameter in the [ListAssessmentRuns \(p. 55\)](#) action.

Contents

completionTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **completedAt** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: [TimestampRange \(p. 128\)](#) object

Required: No

durationRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: [DurationRange \(p. 114\)](#) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string containing a wildcard that is specified for this data type property must match the value of the **assessmentRunName** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **rulesPackages** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

startTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **startTime** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: [TimestampRange \(p. 128\)](#) object

Required: No

stateChangeTimeRange

For a record to match a filter, the value that is specified for this data type property must match the **stateChangedAt** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: [TimestampRange \(p. 128\)](#) object

Required: No

states

For a record to match a filter, one of the values specified for this data type property must be the exact match of the value of the **assessmentRunState** property of the [AssessmentRun \(p. 101\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: `CREATED` | `START_DATA_COLLECTION_PENDING` | `START_DATA_COLLECTION_IN_PROGRESS` | `COLLECTING_DATA` |

Amazon Inspector API Reference Contents

STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | EVALUATING_RULES | FAILED
| COMPLETED | COMPLETED_WITH_ERRORS

Required: No

AssessmentRunNotification

Used as one of the elements of the [AssessmentRun](#) (p. 101) data type.

Contents

date

The date of the notification.

Type: Timestamp

Required: Yes

error

The Boolean value that specifies whether the notification represents an error.

Type: Boolean

Required: Yes

event

The event for which a notification is sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

message

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

snsPublishStatusCode

The status code of the SNS notification.

Type: String

Valid Values: SUCCESS | TOPIC_DOES_NOT_EXIST | ACCESS_DENIED | INTERNAL_ERROR

Required: No

snsTopicArn

The SNS topic to which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

AssessmentRunStateChange

Used as one of the elements of the [AssessmentRun](#) (p. 101) data type.

Contents

state

The assessment run state.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING |
START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA |
STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | EVALUATING_RULES | FAILED
| COMPLETED | COMPLETED_WITH_ERRORS

Required: Yes

stateChangedAt

The last time the assessment run state changed.

Type: Timestamp

Required: Yes

AssessmentTarget

Contains information about an Amazon Inspector application. This data type is used as the response element in the [DescribeAssessmentTargets](#) (p. 26) action.

Contents

arn

The ARN that specifies the Amazon Inspector assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment target is created.

Type: Timestamp

Required: Yes

name

The name of the Amazon Inspector assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn

The ARN that specifies the resource group that is associated with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

updatedAt

The time at which [UpdateAssessmentTarget](#) (p. 94) is called.

Type: Timestamp

Required: Yes

AssessmentTargetFilter

Used as the request parameter in the [ListAssessmentTargets \(p. 58\)](#) action.

Contents

assessmentTargetNamePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTargetName** property of the [AssessmentTarget \(p. 108\)](#) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

AssessmentTemplate

Contains information about an Amazon Inspector assessment template. This data type is used as the response element in the [DescribeAssessmentTemplates](#) (p. 29) action.

Contents

arn

The ARN of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTargetArn

The ARN of the assessment target that corresponds to this assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment template is created.

Type: Timestamp

Required: Yes

durationInSeconds

The duration in seconds specified for this assessment template. The default value is 3600 seconds (one hour). The maximum value is 86400 seconds (one day).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

name

The name of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

rulesPackageArns

The rules packages that are specified for this assessment template.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding from the assessment run that uses this assessment template.

Type: array of [Attribute](#) (p. 113) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

AssessmentTemplateFilter

Used as the request parameter in the [ListAssessmentTemplates](#) (p. 61) action.

Contents

durationRange

For a record to match a filter, the value specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentTemplate](#) (p. 110) data type.

Type: [DurationRange](#) (p. 114) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTemplateName** property of the [AssessmentTemplate](#) (p. 110) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the values that are specified for this data type property must be contained in the list of values of the **rulesPackageArns** property of the [AssessmentTemplate](#) (p. 110) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

AssetAttributes

A collection of attributes of the host from which the finding is generated.

Contents

agentId

The ID of the agent that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

amiId

The ID of the Amazon Machine Image (AMI) that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

autoScalingGroup

The Auto Scaling group of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Addresses

The list of IP v4 addresses of the EC2 instance where the finding is generated.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

Attribute

This data type is used as a request parameter in the [AddAttributesToFindings](#) (p. 4) and [CreateAssessmentTemplate](#) (p. 10) actions.

Contents

key

The attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to the attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

DurationRange

This data type is used in the [AssessmentTemplateFilter \(p. 111\)](#) data type.

Contents

maxSeconds

The maximum value of the duration range. Must be less than or equal to 604800 seconds (1 week).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

minSeconds

The minimum value of the duration range. Must be greater than zero.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

EventSubscription

This data type is used in the [Subscription](#) (p. 125) data type.

Contents

event

The event for which Amazon Simple Notification Service (SNS) notifications are sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED |
ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

subscribedAt

The time at which [SubscribeToEvent](#) (p. 90) is called.

Type: Timestamp

Required: Yes

FailedItemDetails

Includes details about the failed items.

Contents

failureCode

The status code of a failed item.

Type: String

Valid Values: INVALID_ARN | DUPLICATE_ARN | ITEM_DOES_NOT_EXIST | ACCESS_DENIED
| LIMIT_EXCEEDED | INTERNAL_ERROR

Required: Yes

retryable

Indicates whether you can immediately retry a request for this item for a specified resource.

Type: Boolean

Required: Yes

Finding

Contains information about an Amazon Inspector finding. This data type is used as the response element in the [DescribeFindings \(p. 34\)](#) action.

Contents

arn

The ARN that specifies the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assetAttributes

A collection of attributes of the host from which the finding is generated.

Type: [AssetAttributes \(p. 112\)](#) object

Required: No

assetType

The type of the host from which the finding is generated.

Type: String

Valid Values: `ec2-instance`

Required: No

attributes

The system-defined attributes for the finding.

Type: array of [Attribute \(p. 113\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

confidence

This data element is currently not used.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

createdAt

The time when the finding was generated.

Type: Timestamp

Required: Yes

description

The description of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

id

The ID of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

indicatorOfCompromise

This data element is currently not used.

Type: Boolean

Required: No

numericSeverity

The numeric value of the finding severity.
Type: Double
Valid Range: Minimum value of 0.0. Maximum value of 10.0.
Required: No

recommendation

The recommendation for the finding.
Type: String
Length Constraints: Minimum length of 0. Maximum length of 20000.
Required: No

schemaVersion

The schema version of this data type.
Type: Integer
Valid Range: Minimum value of 0.
Required: No

service

The data element is set to "Inspector".
Type: String
Length Constraints: Minimum length of 0. Maximum length of 128.
Required: No

serviceAttributes

This data type is used in the [Finding \(p. 117\)](#) data type.
Type: [InspectorServiceAttributes \(p. 121\)](#) object
Required: No

severity

The finding severity. Values can be set to High, Medium, Low, and Informational.
Type: String
Valid Values: Low | Medium | High | Informational | Undefined
Required: No

title

The name of the finding.
Type: String
Length Constraints: Minimum length of 0. Maximum length of 20000.
Required: No

updatedAt

The time when [AddAttributesToFindings \(p. 4\)](#) is called.
Type: Timestamp
Required: Yes

userAttributes

The user-defined attributes that are assigned to the finding.
Type: array of [Attribute \(p. 113\)](#) objects
Array Members: Minimum number of 0 items. Maximum number of 10 items.
Required: Yes

FindingFilter

This data type is used as a request parameter in the [ListFindings \(p. 67\)](#) action.

Contents

agentIds

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **agentId** property of the [Finding \(p. 117\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

attributes

For a record to match a filter, the list of values that are specified for this data type property must be contained in the list of values of the **attributes** property of the [Finding \(p. 117\)](#) data type.

Type: array of [Attribute \(p. 113\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

autoScalingGroups

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **autoScalingGroup** property of the [Finding \(p. 117\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

creationTimeRange

The time range during which the finding is generated.

Type: [TimestampRange \(p. 128\)](#) object

Required: No

ruleNames

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **ruleName** property of the [Finding \(p. 117\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Maximum length of 1000.

Required: No

rulesPackageArns

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **rulesPackageArn** property of the [Finding \(p. 117\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

severities

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **severity** property of the [Finding \(p. 117\)](#) data type.

Type: array of Strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

userAttributes

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **userAttributes** property of the [Finding \(p. 117\)](#) data type.

Type: array of [Attribute \(p. 113\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

InspectorServiceAttributes

This data type is used in the [Finding \(p. 117\)](#) data type.

Contents

assessmentRunArn

The ARN of the assessment run during which the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

rulesPackageArn

The ARN of the rules package that is used to generate the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

ResourceGroup

Contains information about a resource group. The resource group defines a set of tags that, when queried, identify the AWS resources that make up the assessment target. This data type is used as the response element in the [DescribeResourceGroups \(p. 38\)](#) action.

Contents

arn

The ARN of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which resource group is created.

Type: Timestamp

Required: Yes

tags

The tags (key and value pairs) of the resource group. This data type property is used in the [CreateResourceGroup \(p. 13\)](#) action.

Type: array of [ResourceGroupTag \(p. 123\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

ResourceGroupTag

This data type is used as one of the elements of the [ResourceGroup \(p. 122\)](#) data type.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

RulesPackage

Contains information about an Amazon Inspector rules package. This data type is used as the response element in the [DescribeRulesPackages](#) (p. 41) action.

Contents

arn

The ARN of the rules package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

description

The description of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

name

The name of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

provider

The provider of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

version

The version ID of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

Subscription

This data type is used as a response element in the [ListEventSubscriptions \(p. 64\)](#) action.

Contents

eventSubscriptions

The list of existing event subscriptions.

Type: array of [EventSubscription \(p. 115\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the Amazon Simple Notification Service (SNS) topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Tag

A key and value pair. This data type is used as a request parameter in the [SetTagsForResource \(p. 83\)](#) action and a response element in the [ListTagsForResource \(p. 73\)](#) action.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

A value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

TelemetryMetadata

The metadata about the Amazon Inspector application data metrics collected by the agent. This data type is used as the response element in the [GetTelemetryMetadata \(p. 44\)](#) action.

Contents

count

The count of messages that the agent sends to the Amazon Inspector service.

Type: Long

Required: Yes

dataSize

The data size of messages that the agent sends to the Amazon Inspector service.

Type: Long

Required: No

messageType

A specific type of behavioral data that is collected by the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

TimestampRange

This data type is used in the [AssessmentRunFilter \(p. 104\)](#) data type.

Contents

beginDate

The minimum value of the timestamp range.

Type: Timestamp

Required: No

endDate

The maximum value of the timestamp range.

Type: Timestamp

Required: No

Common Parameters

The following table lists the parameters that all actions use for signing Signature Version 4 requests. Any action-specific parameters are listed in the topic for that action. To view sample requests, see [Examples of Signed Signature Version 4 Requests](#) or [Signature Version 4 Test Suite](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service. For a list of services that support AWS Security Token Service, go to [Using Temporary Security Credentials to Access AWS](#) in *Using Temporary Security Credentials*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the common errors that all actions return. Any action-specific errors are listed in the topic for the action.

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

Throttling

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400